



Clay Modeling Products
Since 1892, the finest name in modeling clay


Chavant, Inc.
5043 Industrial Road
Farmingdale, NJ 07727

1-800-CHAVANT
Fax: (732) 842-3621
Internet: <http://www.chavant.com>
E-mail: mail@chavant.com

MATERIAL SAFETY DATA SHEET

May 23, 2012

HAZARD RATING

	FLAMMABILITY			HAZARD RATING
				
TOXICITY			REACTIVITY	
		SPECIAL		N 4 - EXTREME F 3 - HIGH P 2 - MODERATE A 1 - SLIGHT 0 - INSIGNIFICANT

SECTION 1. PRODUCT IDENTIFICATION

TRADE NAME: Castilene soft, medium and hard

CHEMICAL NAME: Modeling Compound

EMERGENCY PHONE: 1-800-242-8268
1-732-751-0003

EMERGENCY FAX: 1-732-751-1982

SECTION 2. HAZARDOUS INGREDIENT INFORMATION

This product is not hazardous as defined in 29 CFR 1900.1200. The composition of this clay is a trade secret as allowed by 29 CFR 1910.1200-48. In the event of a medical emergency, compositional information will be provided to a physician or nurse.

Product labeling conforms to ASTM D-4236 (no special label required).

SECTION 3. PHYSICAL AND CHEMICAL DATA

Appearance and Odor: Green waxy solid with a slight odor.
Specific Gravity: Varies between 1.05
Solubility in Water: Negligible (<1%)
Evaporation Rate: N/A
Vapor Pressure: N/A
Vapor Density: N/A
Melting Point: 170-190 °F

SECTION 4. HEALTH INFORMATION AND PROTECTION

NATURE OF HAZARD

EYE CONTACT: Direct contact may irritate but will not injure eye tissue.
SKIN CONTACT: Clay is regularly used with no skin protection.
INHALATION: N/A
INGESTION: May induce laxative effects.

FIRST AID

EYE CONTACT: Flush with water.
SKIN CONTACT: Modeling clay is normally used with no skin protection. If irritation appears, it is an allergic reaction and use should be discontinued.
INHALATION: Normally not required.
INGESTION: Normally not required.

SECTION 5. FIRE AND EXPLOSION HAZARD

FLASHPOINT: > 300 °F.
FLAMMABLE LIMITS: N/A
SPECIAL FIRE FIGHTING INFORMATION: Firefighters should use self-contained breathing apparatus to avoid exposure to smoke.

