



Clay Modeling Products
Since 1892, the finest name in modeling clay

Chavant, Inc.
5043 Industrial Road
Farmingdale, NJ 07727

1-800-CHAVANT
Fax: (732) 842-3621
Internet: <http://www.chavant.com>
E-mail: mail@chavant.com

MATERIAL SAFETY DATA SHEET

March 7, 2007

HAZARD RATING

	FLAMMABILITY		<u>HAZARD RATING</u>
TOXICITY		REACTIVITY	N 4 - EXTREME F 3 - HIGH P 2 - MODERATE A 1 - SLIGHT 0 - INSIGNIFICANT
	SPECIAL		

SECTION 1. PRODUCT IDENTIFICATION

TRADE NAMES: CM-50, CM-70, DaVinci, H-525, I-305, I-307, J-88, J-525, Professional Plasteline

CHEMICAL NAME: Sulfur-Based Modeling Clay

EMERGENCY PHONE: 1-800-242-8268
1-732-751-0003

EMERGENCY FAX: 1-732-751-1982

SECTION 2. HAZARDOUS INGREDIENT INFORMATION

This product is not hazardous as defined in 29 CFR1900.1200. The composition of this clay is a trade secret as allowed by 29 CFR 1910. 1200-48. In the event of a medical emergency, compositional information will be provided to a physician or nurse.

Product labeling conforms to ASTM D-4236 (no special label required).

SECTION 3. PHYSICAL AND CHEMICAL DATA

Appearance and Odor: Brown or green, pliable solid, varying degree of odor.

Specific Gravity: Varies between 1.47 and 1.76 g/cm³ depending on formula.

Solubility in Water: Negligible (<1%)

Evaporation Rate: N/A

Vapor Pressure: N/A

Vapor Density: N/A

Melting Point: 180 - 200 °F

SECTION 4. HEALTH INFORMATION AND PROTECTION

NATURE OF HAZARD

EYE CONTACT: Direct contact may irritate but will not injure eye tissue.

SKIN CONTACT: Clay is regularly used with no skin protection. Hypersensitive users may experience slight irritation.

INHALATION: N/A

INGESTION: May induce laxative effects.

FIRST AID

EYE CONTACT: Flush with water.

SKIN CONTACT: Modeling clay is normally used with no skin protection. If irritation appears, it is an allergic reaction and use should be discontinued.

INHALATION: Normally not required.

INGESTION: Normally not required.

SECTION 5. FIRE AND EXPLOSION HAZARD

FLASHPOINT: > 200 °F.

FLAMMABLE LIMITS: N/A

SPECIAL FIRE FIGHTING INFORMATION: Firefighters should use self-contained breathing apparatus to avoid exposure to smoke and vapor. A component, SULFUR, often burns in air to form Sulfur Dioxide.

